

# Progressive distributors MX-F modular system

These progressive distributors can be modularly assembled until the desired lubricant quantity is reached. The individual disklike components are available in different predefined volumes and thereby deliver the precise amount of lubricant.

Progressive distributor MX-F consists of one initial element (without delivery piston), three to eleven middle elements and an end element. The middle elements are available in four different delivery volumes ranging from 25 mm<sup>3</sup> to 105 mm<sup>3</sup>.

End elements can also be supplied with four different delivery volumes. Only the end elements are available with in-built proximity switch (see table).



Technical data		
Operating pressure	max. 300 bar	
Temperature	-35 °C to + 100 °C	
Medium	oil, fluid grease, grease	
Connection	M 10x1	
<b>Initial elements</b> <span style="background-color: yellow; border-radius: 50%; padding: 2px;">3</span>	<b>Ord.no.</b>	
Initial element	<b>14528</b>	
Connecting rod for	6 outlets	<b>14539</b>
Connecting rod for	8 outlets	<b>14540</b>
Connecting rod for	10 outlets	<b>14541</b>
<b>Middle elements</b> <span style="background-color: yellow; border-radius: 50%; padding: 2px;">4</span>	<b>Output</b>	<b>Ord.no.</b>
MX-F 25	25 mm <sup>3</sup> /stroke	<b>14529</b>
MX-F 45	45 mm <sup>3</sup> /stroke	<b>14530</b>
MX-F 75	75 mm <sup>3</sup> /stroke	<b>14531</b>
MX-F 105	105 mm <sup>3</sup> /stroke	<b>14532</b>
<b>End elements</b> <span style="background-color: yellow; border-radius: 50%; padding: 2px;">5</span>	<b>Ord.no.</b>	
MX-F 25	<b>14533</b>	
MX-F 45	<b>14534</b>	
MX-F 75	<b>14535</b>	
MX-F 105	<b>14536</b>	
MX-F 75 with proximity switch	<b>14537</b>	
MX-F 105 with proximity switch	<b>14538</b>	
<b>Mounting accessories</b> <span style="background-color: yellow; border-radius: 50%; padding: 2px;">6</span>	<b>Ord.no.</b>	
Seal kit	<b>14543</b>	
Check valve	<b>14544</b>	
Connecting cable 5 m	<b>14546</b>	
Distributor bridge	<b>14547</b>	
Lock screw for closing outlets	<b>14548</b>	
Lock screw Separation of internal outlets	<b>14549</b>	
<b>More variations and outlets on request</b>		

